N-CHANNEL MOS FIELD EFFECT POWER TRANSISTOR

2SK591

DESCRIPTION The 2SK591 is N-Channel MOS Field Effect Power Transistor designed for solenoid, motor and lamp driver.

FEATURES

- 4 V Gate Drive – Logic level –
- Low $R_{DS(on)}$
- No Secondary Breakdown

PACKAGE DIMENSIONS
in millimeters (inches)



ABSOLUTE MAXIMUM RATINGS

Maximum Temperatures
- Storage Temperature . . . . . −55 to + 150 °C
- Channel Temperature . . . . . 150 °C Maximum

Maximum Power Dissipations
- Total Power Dissipation (T_a = 25 °C) . . . 2.0 W
- Total Power Dissipation (T_c = 25 °C) . . . 35 W

Maximum Voltages and Currents (T_a = 25 °C)
- V_{DSS} Drain to Source Voltage . . . . . 60 V
- V_{GSS} Gate to Source Voltage . . . . . ±20 V
- $I_{D(DC)}$ Drain Current (DC) . . . . . ±15 A
- $I_{D(pulse)}$ Drain Current (pulse)* . . . . . ±60 A

*PW ≦ 300 μs, Duty Cycle ≦ 10 %

ELECTRICAL CHARACTERISTICS (T_a = 25 °C)

SYMBOL	CHARACTERISTIC	MIN.	TYP.	MAX.	UNIT	TEST CONDITIONS
$R_{DS(on)}$	Drain to Source On-State Resistance			0.055	Ω	V_{GS} = 10 V, I_D = 6 A
$R_{DS(on)}$	Drain to Source On-State Resistance			0.070	Ω	V_{GS} = 4 V, I_D = 6 A
$V_{GS(off)}$	Gate to Source Cutoff Voltage	1		2.5	V	V_{DS} = 10 V, I_D = 1 mA
$\|Y_{fs}\|$	Forward Transfer Admittance	5			S	V_{DS} = 10 V, I_D = 6 A
I_{DSS}	Drain Leakage Current			10	μA	V_{DS} = 60 V, V_{GS} = 0
I_{GSS}	Gate to Source Leakage Current			±100	nA	V_{GS} = ±20 V, V_{DS} = 0
C_{iss}	Input Capacitance		1800		pF	V_{DS} = 10V
C_{oss}	Output Capacitance		800		pF	V_{GS} = 0
C_{rss}	Reverse Transfer Capacitance		350		pF	f = 1 MHz
$t_{d(on)}$	Turn On Delay Time		20		ns	
t_r	Rise Time		85		ns	I_D = 6 A, V_{CC} ≒ 30 V
$t_{d(off)}$	Turn Off Delay Time		240		ns	R_L = 5 Ω, $V_{GS(on)}$ = 10 V
t_f	Fall Time		230		ns	R_{in} = 10 Ω

TYPICAL CHARACTERISTICS (T_a = 25 °C)

DERATING FACTOR OF FORWARD BIAS SAFE OPERATING AREA



FORWARD BIAS SAFE OPERATING AREA



TOTAL POWER DISSIPATION vs. AMBIENT TEMPERATURE



DRAIN CURRENT vs. DRAIN TO SOURCE VOLTAGE



FORWARD TRANSFER ADMITTANCE vs. DRAIN CURRENT



SOURCE TO DRAIN DIODE FORWARD VOLTAGE



CAPACITANCE vs. DRAIN TO SOURCE VOLTAGE



DRAIN TO SOURCE ON-STATE RESISTANCE vs. GATE TO SOURCE VOLTAGE



DRAIN TO SOURCE ON-STATE RESISTANCE vs. CHANNEL TEMPERATURE









SWITCHING TIME TEST CIRCUIT